Shaker Waterbath for butyrometers



Anwendung:

Shaker Water Bath with 3 supports a 12 drillings for butyrometers::

- high precision
- high safety standard
- available with revolution pump

Technical Data:

Casing:	Polypropylene (PP) white Material strength 10 mm
Operation:	keypad
Controller:	Microprocessor control
Temperature Range:	10°C bis 95°C + / – 0,3°C (depending on model) minimum temperature depending on ambient temperature
Setting range:	10°C bis 99°C
Safety:	Switch-off in event of overheating, sensor break-down, water shortage
Heating element:	Chromium nickel steel
Power supply:	230 VAC
Drive for support:	Induction motor 15 watt
rotation moving:	200 RPM

Order Details:

Aerne Analytic e. K. - Dekan-Schmid-Str. 11- D-89264 Weißenhorn
Tel: +49 (0)7309-92 75 077 -Fax: +49 (0)7309-92 75 076
email: info@aerne-analytic.de

Payload Dimensions in cm LxBxH	Number Butyrometers	Performance/ Watt	Order-No.
33×22,5×25	3 x 12	2000	AETSWB
Water Bath Eurotherm II			
Stand /pcs.			Stativ

Aerne Analytic e. K. - Dekan-Schmid-Str. 11- D-89264 Weißenhorn
Tel: +49 (0)7309-92 75 077 -Fax: +49 (0)7309-92 75 076
email: info@aerne-analytic.de